

1 19A NCAC 03D .0529 is proposed for readoption without substantive changes as follows:

2

3 **19A NCAC 03D .0529 CERTIFICATION**

4

5 When the vehicle has been approved, the ~~inspection mechanic shall~~ following shall occur:

- 6 (1) ~~Prepare the appropriate sticker (safety equipment or safety equipment/exhaust emission) for~~  
7 ~~affixing to the vehicle.~~
- 8 (2) ~~Remove the old inspection sticker from the windshield.~~
- 9 (3) ~~Follow the instructions on the "Inspection Sticker."~~
- 10 (4) ~~Place the "Inspection Sticker" on the inside of windshield at the bottom of the left side so that the~~  
11 ~~edge of the sticker is no more than one inch from the left side of the windshield. Platforms are~~  
12 ~~required for glass plastic windshields.~~
- 13 (5) ~~For vehicles without windshields, issue motorcycle/trailer stickers or non windshield~~  
14 ~~safety/emission stickers. The sticker shall be placed on the left side of vehicle as near the front as~~  
15 ~~possible.~~
- 16 (6)(1) ~~List the total inspection repair charges made, if any, on the "Receipt and Statement" form along~~  
17 ~~with the serial number of the inspection sticker which was attached to the inspected vehicle. A~~  
18 ~~Safety Equipment On Board Diagnostic (OBD)Exhaust-Emission ~~inspection mechanic~~ Inspection~~  
19 ~~Mechanic must enter all required information into the analyzer.~~
- 20 (7)(2) Collect fees as described in G.S. 20-183.7.
- 21 (8)(3) Sign and give the original of the "Receipt and Statement" Receipt and Statement form to the  
22 operator or owner.

23

24 *History Note: Authority G.S. 20-2; 20-39; 20-183.4D; 20-183.7;*  
25 *Eff. October 1, 1994.*  
26 *Readopted Eff. \_\_\_\_\_, 2021.*